

Serial No.: 10/788,620

### AMENDMENT TO THE CLAIMS

1. (Currently Amended) A method of providing communication between a telephone caller and a callee of the telephone call, comprising:

[[a)] linking a switched telephone network with an internet network via a telephone network/internet domain network interface;

~~b) detecting~~ receiving an attempted call at a switching center within the switched telephone network;

determining that the attempted call cannot be routed beyond the switching center;

~~e) upon detection of the attempted call;~~ having the switched telephone network inform the telephone network/internet domain network interface to provide a message reporting details of the attempted call to the callee via the internet network.

2. (Original) The method of providing communication between a telephone caller and a callee of the telephone call according to Claim 1, wherein the switched telephone network is a public switched telephone network.

Serial No.: 10/788,620

3. (Original) The method of providing communication between a telephone caller and a callee of the telephone call according to Claim 2, wherein the internet network is the public Internet.

4. (Currently Amended) The method of providing communication between a telephone caller and a callee of the telephone call according to Claim 3, wherein the public switched telephone network informs the telephone network/internet domain network interface to provide the message via an Internet protocol to the callee of the public switched telephone network call when an abnormality is detected in the public switched telephone network which prevents the public switched telephone network from ~~completing the call connection between the caller and the callee~~ routing the call beyond the switching center.

5. (Original) The method of providing communication between a telephone caller and a callee of the telephone call according to Claim 4, wherein the telephone network/internet domain network interface provides the message via an Internet protocol to a caller-selected list of recipients as well as the callee of the public switched telephone network call.

Serial No.: 10/788,620

6. (Original) A method of providing communication between a telephone caller and a callee of the telephone call according to Claim 1, wherein the callee informs at least one of the public switched telephone network or the Internet domain network interface to provide the message to the callee in real time via an Internet protocol when the attempted call is intended for the telephone number of the callee.

7. (Original) A method of providing communication between a telephone caller and a callee of the telephone call according to Claim 1, wherein the message details at least one of the telephone number trying to reach the callee, the caller identification of the telephone number trying to reach the callee, and the time of the attempted call.

8. (Original) A method of providing communication between a telephone caller and a callee of the telephone call according to Claim 1, wherein the message is an Instant Message provided in real time.

Serial No.: 10/788,620

9. (Original) A method of providing communication between a telephone caller and a callee of the telephone call according to Claim 1, wherein the message is a text message.

10. (Original) A method of providing communication between a telephone caller and a callee of the telephone call according to Claim 1, wherein the message is an email.

11. (Currently Amended) A method of providing communication between a telephone caller and a callee of the telephone call, comprising:

[[a]] linking a public switched telephone network with an Internet domain network via a service control point extension for the public switched telephone network and an SIP proxy server for an Internet domain network service provider;

[[b]] detecting at a switching center of the public switched telephone network an attempted ~~public switched telephone network (public switched telephone network)~~ call within the public switched telephone network;

Serial No.: 10/788,620

~~e) upon detection of the attempted public switched telephone network call, determining that the attempted call cannot be routed beyond the switching center;~~  
and

having the public switched telephone network inform the Internet domain network service provider to provide a message reporting details of the attempted call in real time to the callee of the public switched telephone network call via an Internet protocol.

12. (Canceled)

13. (Currently Amended) A method of providing crossover services, between an internet domain and a switched telephone network domain comprising the steps of:

a) starting an IM agent for a caller on an Internet-capable device to express interest in providing outgoing call notifications of the caller to the callee or other designated phone lines;

b) having the IM agent register the preference of the caller with the telephone network to inform callees about an attempt by the caller to call the callee or any of the designated telephone lines,

Serial No.: 10/788,620

c) having the telephone network authenticate the IM agent and register the Internet address of the IM agent and the preferences of the caller;[[.]]

d) having the telephone network undertake appropriate actions to ensure that outgoing calls to the callee or designated telephone lines identified in step b) result in a notification action to the callee list when a telephone network service failure is detected within the telephone network and a voice-based communication cannot be delivered to the callee through the telephone network;

e) executing the actions in Step d) when a telephone network ~~interruption/service~~ service failure is detected within the telephone network including having the telephone network capture the incoming call information; ~~and~~

f) automatically creating a message out of the ~~incoming~~ outgoing call information;

g) routing the message through the Internet to the Internet address of the IM agent of the callee or designated telephone lines registered in step c); and

h) displaying the message in Internet-capable devices of the callee, or of persons on the list of designated telephone lines, wherein the message through the Internet is the only message received by the callee or the persons on the list of designated telephone lines.

Serial No.: 10/788,620

14. (New) A method of providing communication between a telephone user and an Internet user, comprising:

linking a public switched telephone network with an Internet domain network via a service control point extension for the public switched telephone network and an SIP proxy server for an Internet domain network service provider;

detecting a detection point within the public switched telephone network caused by a telephone of the telephone user, wherein the detection point indicates that the telephone user disconnected the telephone before the public switched telephone network is able to complete any call;

having the public switched telephone network inform the Internet domain network service provider to provide a message to the Internet user reporting the detection point of the telephone user via an Internet protocol.

15. (New) The method of Claim 14, wherein the detection point indicates the telephone user abandoned the telephone use before signaling any call was completed.